


# **Key Features in ODS Graphics for Efficient Clinical Graphing**

Yuxin (Ellen) Jiang


BASUG  
March 23, 2016

# SAS Data Visualization is Improving!



Grouped Timeline

2014/06/16




Lab Values Panel

2014/06/07




PharmaSUG 2014

2014/06/05




The HIGHLOW Plot

2014/05/04




Multi-Group Series Plots

2014/04/27




Labeled Curves

2014/04/20



The BLOCK Plot

2014/04/14



G100 with SGPLOT

2014/04/06



SGF 2014

2014/03/28

# Introduction

- **New features in SG PROCs and GTL:**
  - 1) Plots overlay in single-cell or multi-cell graphs
  - 2) Flexible ways to control graph appearance
  - 3) Enhanced annotation
  - 4) Plots overlay in multi-cell graphs
  - 5) Classification panel of multiple plots with individualized labeling

# Statistical Graphics (SG) Procedures and Graphic Template Language (GTL)

- **SG Procedures**

- For programmers to create commonly used graphs

- SGPLOT

- SGPANEL

- SGSCATTER

- **GTL**

- For programmers to create highly customized complex graphs


# Feature1: Better Control of Axes in Different Scales and Intervals

- In SGPLOT, the default axis scale is automatically chosen based on the variable types on the axis. If a numeric variable on the axis, a linear scale axis will be automatically set as default for the axis.
- In GPLOT, it's not straightforward when data are collected at uneven intervals, a plot with equal-width intervals will be incorrectly generated and SAS log will have a warning.

# Feature1: Better Control of Axes in Different Scales and Intervals


## SGPLOT – New

Default listing style



axis values=(0 1 3 5 7 10  
14 21 28);

## GPLOT –Old





axis1 order=(0 1 3 5 7 10  
14 21 28);

## Feature 2: Flexible Ways to Control Graph Appearance

- ▶ Pre-defined **ODS style templates**
- ▶ **STYLEATTRS**, a new enhancement in SAS 9.4, conveniently modify frequently changed figure attributes such as colors, line patterns and data symbols in SGPLOT and GTL .
- ▶ In statement **LINEATTRS** or **MARKERATTRS** options to customize attributes for individual plot

# Feature 2: Flexible Ways to Control Graph Appearance





## Feature 2: Flexible Ways to Control Graph Appearance

```
proc template;❶
  define style mystyle;
    parent=styles.listing;
    style GraphData1 from GraphData1 / MarkerSymbol = "circle";
    style GraphData2 from GraphData2 / MarkerSymbol = "X";
  end;
run;
ods rtf file = "&filename..rtf" style=mystyle ❶;
proc sgplot data=final;
  styleattrs datasymbols=(Circle X)
    datacontrastcolors=(purple green); [❷ SAS 9.4]
  series x=xaxis y=mean /group=trtpn lineattrs=(size=1) ❸ ;
  scatter x=xaxis y=mean /group=trtpn yerrorlower=lower
    yerrorupper=upper markerattrs=(size=7) ❸;
  .....
run;
ods rtf close;
```

## Feature 2: Flexible ways to control graph appearance – compare to old GPLOT


In GPLOT, those attributes such as symbol, color and size have to be set by SYMBOL statement or create template outside PROC GPLOT.

```
symbol1 interpol=hiloctj color=blue line=1 height=6;  
symbol2 interpol=hiloctj color=red line=2 height=6;  
symbol3 interpol=none color=blue value=circle height=2;  
symbol4 interpol=none color=red value=square height=2;
```

```
Axis1 order=(0 1 3 5 7 10 14 21 28) label='days' ;  
Axis2 label=(angle=90) order=(&yaxis) label=('Results') ;  
Proc gplot data=reshape;  
    plot yvar*xvar=trtpn / haxis=axis1 vaxis=axis2 legend=legend1;  
    plot2 mean*xvar=trtpn / vaxis=axis2 noaxis nolegend;  
run;
```

# Feature 3: Enhanced annotation

- ▶ %SGANNO graph annotation facilities
- ▶ AXISTABLE is a new feature in SAS 9.4, which prints a table of counts(N) on the bottom of the plot either inside or outside the plot.



**%sganno;**

data anno;

**%sgarrow**(x1=14,y1=285,x2=14,y2=270,  
shape='filled', linethickness=1, scale=0.2,  
x1space='datavalue', ....);

**%sgtext**(label="Midpoint", x1=13,y1=300,  
width=22, widthunit="data", textsize=10.5,  
textcolor='black',x1space='datavalue', ... );


run;

proc sgplot data=final **sganno=anno**;

**xaxistable** n / x=xaxis class=trt location=inside colorgroup=trt separator;

# Feature 4.1: Plots overlay by GTL

Biomarker test summary



## Feature 4.2: Structure of Layout Containers

- ❶ **PROC TEMPLATE** and **PROC SGRENDER** to create and apply overall layout template.
- ❷ **Two LAYOUT LATTICE** statements define the position(ROWS=,COLUMNS=) and the size of each layout container (COLUMNWEIGHTS =)
- ❸ **Three LAYOUT OVERLAY** statements pairing up with **END OVERLAY** create blocks which define the plots in three layout container.

```

proc template; ❶
define statgraph gtl_overlay;
begingraph / datacontrastcolors=(darkblue darkred) datasymbols=(circle triangle)
    datalinepatterns=(dash solid);
entrytitle halign=center "Biomarker test summary" / textattrs=(size=11.7pt) haligncenter=graph;
    layout lattice /rows=1 columns=2 columnweights=(0.4 0.6) columngutter=.5cm; ❷
        layout lattice / rows=2 columns=1 rowgutter=.5cm; ❷
            layout overlay / xaxisopts=(label="Test A" labelAttrs=(Weight=bold)) ❸
                yaxisopts=(griddisplay=on label="Test B" labelAttrs=(Weight=bold));
                scatterplot x=v1 y=v2/group=trtp1;
                regressionplot x=v1 y=v2/group=trtp1;
            endlayout;

            layout overlay / xaxisopts=(label="Day" labelAttrs=(Weight=bold)) ❸
                yaxisopts=(griddisplay=on label="Mean of Test C")
                barchart category=day response=v3/group=grp stat=mean groupdisplay=cluster;
            endlayout;
        endlayout;

        layout overlay/<option1>; ❸
            seriesplot x=xvar y=mean_ratio / group=grpc display=(markers) name="1";
            scatterplot x=xvar y=mean_ratio/ group=grpc primary=true
                yerrorupper=upper_ratio yerrorlower=lower_ratio ;

            innermargin / align=bottom opaque=true separator=true;
                ❹ axistable value=n_ratio x=day/includemissingclass=false [SAS 9.4]
                    headerLabel="Evaluable subjects (n)" labelPosition=min class=grpc
                    valueattrs=(size=7) colorgroup=grpc;
            endinnermargin;

            discreteLegend "1" / Location=Inside across=1 halign=left valign=top Border=false;
        endlayout;
    endlayout;
endgraph;
end;
run;

```

proc sgrender data = final template = gtl\_overlay;


## Feature 5: Classification Panel with Individualized Labeling - SG PANEL

- ❶ **PANELBY**, by subject classification panel layout with one subject per cell.
- ❷ **DATALABEL**, add annotation to data points, make the figure more informative.

```
proc sgpanel data=fix ;  
❶ panelby id/ layout=panel rows=3 columns=2 spacing=10 ;  
  series x=xvar y=yvar / group=grp lineattrs=(pattern=solid) markers  
  ❷ datalabel=grpname name='l';  
  scatter x=xvar y=yvar / group=grp markerattrs=(size=7) name='s';  
  rowaxis min=1 max=100 minor type=log logbase=10  
    LOGSTYLE=LOGEXPAND valueattrs=(size=9) label= 'Results';  
  colaxis min=0 values=(0 1 2 3 5 7) valueattrs=(size=9) label='Days';  
  refline 5 10 50 / transparency = 0.8 ;  
run;
```

# Feature 5.1: Create classification panel


① `panelby id/ layout=panel rows=3 columns=2 spacing=10;`





## Feature 5.2: individualized labeling

Series x=xvar y=yvar / group=grp lineattrs=(pattern=solid)  
markers ② **datalabel=grpname** name='l';



# Conclusion

- ▶ As SAS keeps adding new enhancements in ODS Graphics, it provides powerful flexibility to make clinical graphing much more effective and efficient.
- ▶ Coding of graphs become much clearer and easier with ODS Graphics tools .
- ▶ The best way to learn is to USE IT!

# Acknowledgments

## **BASUG**

My colleagues:

**Mr. Mark McLaughlin**

**Mr. Arthur Collins**

**Hemophilia team**

**Daclizumab team**



Q & A

yuxin.jiang@biogen.com